



SE SPLIT EYELET MOUNTING CLAMPS



Split Eyelets

TYPICAL APPLICATIONS:


Anywhere an alternate connection to pipe is desired. Eliminates:

- Threading
- Brazing
- Welding

CONSTRUCTION:

The split eyelet consists of a top and bottom clamp, two retaining bolts, an outlet body and an O-ring. Clamps and retaining bolts are zinc-plated steel. Standard materials for the body are brass, 303 stainless steel and 316 stainless steel. The O-ring seal is Buna-N.

For Pipe Size	Model	Max. Flow	Drill Size
1/2	1/2X1/8FSE	3.5	9/16
	1/2X1/4FSE	3.5	9/16
3/4	3/4X1/8FSE	3.5	9/16
	3/4X1/4FSE	3.5	9/16
1"	1X1/8FSE	3.5	9/16
	1X1/4FSE	3.5	9/16
	1X3/8FSE	3.5	9/16
1-1/4	1-1/4X1/8FSE	19	11/16
	1-1/4X1/4FSE	19	11/16
	1-1/4X3/8FSE	19	11/16
1-1/2	1-1/2X1/8FSE	19	11/16
	1-1/2X1/4FSE	19	11/16
	1-1/2X3/8FSE	19	11/16
2"	2X1/8FSE	19	11/16
	2X1/4FSE	19	11/16
	2X3/8FSE	19	11/16
2-1/2	2-1/2X1/8FSE	19	11/16
	2-1/2X1/4FSE	19	11/16
	2-1/2X3/8FSE	19	11/16



MODEL SIZE	L	A	C
1/2 SE	1"	2 1/4	1 3/4
3/4 SE	1"	2 1/4	2"
1 SE	1"	2 3/8	2 1/4
1 1/4 SE	1 1/2	3"	2 1/2
1 1/2 SE	1 1/2	3"	2 7/8
2 SE	1 1/2	3 1/2	3 1/2
2 1/2 SE	1 1/2	4"	4"