






MODEL ZS SERIES SPRAY NOZZLE



Also available with Tabz®



CHARACTERISTICS:

BEX Molded Plastic Zip-Tip® Spray Nozzles are designed to allow fast and easy installation and removal of spray nozzle tips and adapters, while providing positive alignment of spray pattern. Double VITON® O-Ring seals are supplied standard with each nozzle tip. Seals are located on, and removed with, the nozzle tip for easy flushing. A variety of models and spray patterns are available.

CONSTRUCTION:

Molded plastic spray nozzles are available in glass reinforced polypropylene or PVDF (Kynar®). Other materials are available upon request. All models are available in either NPT or BSPT threads. (NOTE: Metal and molded plastic ZIP-TIP® components are not interchangeable.)

TYPICAL APPLICATIONS:

- Spray Washing & Rinsing
- Parts Cleaning
- Pretreatment

Model	Max. Free Passage (in)	CAPACITY AT VARIOUS PRESSURES (USGPM)												SPRAY ANGLE @ (degrees)		
		3 psi	5 psi	7 psi	10 psi	15 psi	20 psi	30 psi	40 psi	60 psi	80 psi	100 psi	150 psi	7 psi	20 psi	80 psi
ZS1	0.033	0.06	0.07	0.08	0.10	0.12	0.14	0.17	0.20	0.25	0.28	0.32	0.39	--	55	52
ZS1.5	0.046	0.08	0.11	0.13	0.15	0.18	0.21	0.26	0.30	0.37	0.42	0.47	0.58	--	65	57
ZS2	0.051	0.11	0.14	0.17	0.20	0.25	0.28	0.35	0.40	0.49	0.57	0.63	0.77	54	59	60
ZS3	0.051	0.16	0.21	0.25	0.30	0.37	0.42	0.52	0.60	0.73	0.85	0.95	1.16	50	53	60
ZS3.5	0.051	0.19	0.25	0.29	0.35	0.43	0.50	0.61	0.70	0.86	0.99	1.11	1.36	48	58	61
ZS5	0.064	0.27	0.35	0.42	0.50	0.61	0.71	0.87	1.00	1.22	1.41	1.58	1.94	58	68	62
ZS6	0.064	0.33	0.42	0.50	0.60	0.73	0.85	1.04	1.20	1.47	1.70	1.90	2.32	67	72	70
ZS6.5	0.091	0.36	0.46	0.54	0.65	0.80	0.92	1.13	1.30	1.59	1.84	2.06	2.52	48	56	50
ZS7.5	0.091	0.41	0.53	0.63	0.75	0.92	1.06	1.30	1.50	1.84	2.12	2.37	2.90	55	65	48
ZS8.5	0.091	0.41	0.53	0.63	0.75	0.92	1.06	1.30	1.50	1.84	2.12	2.37	2.90	58	65	63
ZS10	0.091	0.55	0.71	0.84	1.00	1.22	1.41	1.73	2.00	2.45	2.83	3.2	3.9	55	65	50
ZS14	0.091	0.77	0.99	1.17	1.40	1.71	1.98	2.42	2.80	3.4	4.0	4.4	5.4	78	85	75
ZS15	0.102	0.82	1.06	1.26	1.50	1.84	2.12	2.60	3.00	3.7	4.2	4.7	5.8	63	65	60
ZS18	0.102	0.99	1.27	1.51	1.80	2.20	2.55	3.12	3.6	4.4	5.1	5.7	7.0	85	88	76
ZS20	0.102	0.11	0.14	0.17	0.20	0.25	0.28	0.35	0.40	0.49	0.57	0.63	0.77	76	82	75
ZS22	0.114	1.20	1.56	1.84	2.20	2.69	3.11	3.8	4.4	5.4	6.2	7.0	8.5	76	78	76