





ZGS SERIES SPRAY NOZZLES

FULL CONE • THREADED CONNECTION • TWO-PIECE



SPRAY CHARACTERISTICS:

Full cone spray pattern, with uniform distribution throughout the cone.

TYPICAL APPLICATIONS:

- Chemical Processing
- Cooling Sprays
- Continuous Casting
- Foam Breaking

CONSTRUCTION:

Two piece body + removable insert. The nozzle contains a patented insert with larger flow passages, and is less susceptible to clogging.



NOZZLE NPT PIPE SIZE	Length L (in)	Dim. A (in)
1/8ZGS	1.98	0.97
1/4ZGS	2.12	0.97
3/8ZGS	2.56	0.97
1/2ZGS	2.63	0.97
1/2ZLGS	2.79	1.25
3/4ZLGS	2.87	1.25

Model #	Capacity											Spray Angle		
	0.3 bar	0.5 bar	0.7 bar	1.0 bar	1.5 bar	2 bar	3 bar	4 bar	5 bar	6 bar	8 bar	0.5 bar	1.5 bar	5 bar
ZGS1	0.250	0.32	0.38	0.46	0.56	0.64	0.79	0.91	1.02	1.12	1.29	--	55°	52°
ZGS1.5	0.37	0.48	0.57	0.68	0.84	0.97	1.18	1.37	1.53	1.67	1.93	--	65°	57°
ZGS2	0.50	0.64	0.76	0.91	1.12	1.29	1.58	1.82	2.04	2.23	2.58	54°	59°	60°
ZGS3	0.75	0.97	1.14	1.37	1.67	1.93	2.37	2.73	3.06	3.3	3.9	50°	53°	60°
ZGS3.5	0.87	1.13	1.33	1.60	1.95	2.26	2.76	3.2	3.6	3.9	4.5	48°	58°	61°
ZGS5	1.25	1.61	1.91	2.28	2.79	3.2	3.9	4.6	5.1	5.6	6.4	60°	75°	70°
ZGS6	1.50	1.93	2.29	2.73	3.3	3.9	4.7	5.5	6.1	6.7	7.7	67°	72°	70°
ZGS6.5	1.62	2.09	2.48	2.96	3.6	4.2	5.1	5.9	6.6	7.3	8.4	48°	56°	70°
ZGS7.5	1.87	2.42	2.86	3.4	4.2	4.8	5.9	6.8	7.6	8.4	9.7	55°	65°	48°
ZGS8.5	2.12	2.74	3.2	3.9	4.7	5.5	6.7	7.7	8.7	9.5	11.0	58°	65°	63°
ZGS10	2.50	3.2	3.8	4.6	5.6	6.4	7.9	9.1	10.2	11.2	12.9	60°	65°	62°
ZGS14	3.5	4.5	5.3	6.4	7.8	9.0	11.1	12.8	14.3	15.6	18.0	78°	85°	75°
ZGS15	3.7	4.8	5.7	6.8	8.4	9.7	11.8	13.7	15.3	16.7	19.3	63°	65°	60°
ZGS18	4.5	5.8	6.9	8.2	10.0	11.6	14.2	16.4	18.3	20.1	23.2	85°	88°	76°
ZGS20	5.0	6.4	7.6	9.1	11.2	12.9	15.8	18.2	20.4	22.3	25.8	76°	82°	75°

