




CW Series

Wide 150° spray angle for maximum coverage in tight or shallow spaces.




CW Series



Male Thread



Female Thread



Spray Characteristics

The CW series hydraulic atomizing nozzles are meticulously crafted to generate a very fine hollow-cone spray pattern with a wide spray angle, solely utilizing the liquid pressure for atomization. These nozzles are easy to disassemble, assemble, and clean. Standard spray angle is 150° at 40 PSI.

Model Number	"L"	BODY	CAP
¼ FCLW	1	11/16 HEX	11/16 HEX
¼ CW	1	11/16 HEX	11/16 HEX



Construction

Two piece body with removable cap and core. Bodies are available in a variety of materials. The cap and core are supplied in 316 stainless steel standard.

Standard Materials

- B** Brass
- 3** 303 Stainless Steel
- 6** 316 Stainless Steel

Typical Applications

- ✓ Humidifications/Moisture Addition
- ✓ Evaporative Cooling
- ✓ Steam De-superheating

CW Series



Model #		Capacities at Various Pressures USGPH								
Female	Male	30 psi	40 psi	80 psi	100 psi	200 psi	300 psi	500 psi	700 psi	1000 psi
1/4FC5.9W	1/4C5.9W	1.59	1.83	2.59	2.89	4.1	5.0	6.5	7.7	9.2
1/4FC7.4W	1/4C7.4W	1.99	2.30	3.2	3.6	5.1	6.3	8.1	9.6	11.5
1/4FC9.2W	1/4C9.2W	2.47	2.85	4.0	4.5	6.4	7.8	10.1	11.9	14.3
1/4FC12W	1/4C12W	3.2	3.7	5.3	5.9	8.3	10.2	13.2	15.6	18.6
1/4FC14W	1/4C14W	3.8	4.3	6.1	6.9	9.7	11.9	15.4	18.2	21.7
1/4FC18W	1/4C18W	4.8	5.6	7.9	8.8	12.5	15.3	19.7	23.4	27.9
1/4FC23W	1/4C23W	6.2	7.1	10.1	11.3	16.0	19.5	25.2	29.9	36
1/4FC28W	1/4C28W	7.5	8.7	12.3	13.7	19.4	23.8	30.7	36	43