




ZHGSW SERIES SPRAY NOZZLES

FULL CONE • ZIP-TIP CONNECTION • TWO-PIECE



SPRAY CHARACTERISTICS:

A wide angle full cone spray pattern, with uniform distribution throughout the cone.

TYPICAL APPLICATIONS:

- Chemical Processing
- Cooling Sprays
- Continuous Casting
- Foam Breaking

CONSTRUCTION:

Two piece body + removable insert. Sprays at right angle to pipe. The nozzle contains a patented insert with larger flow passages, and is less susceptible to clogging.



NOZZLE PIPE SIZE	Length L (in)	Dim. A (in)
1/8ZHGSW	2.11	1.48
1/4ZHGSW	2.21	1.60
3/8ZHGSW	2.24	1.65
1/2ZHGSW	2.31	1.80
1/2ZLHGSW	2.96	1.71
3/4ZLHGSW	3.04	1.86

Model #	Capacity												Spray Angle		
	3 psi	5 psi	7 psi	10 psi	15 psi	20 psi	30 psi	40 psi	60 psi	80 psi	100 psi	150 psi	7 psi	20 psi	80 psi
ZHGS2.8W	0.153	0.198	0.234	0.280	0.34	0.40	0.48	0.56	0.69	0.79	0.89	1.08	110°	105°	96°
ZHGS4.3W	0.236	0.304	0.36	0.43	0.53	0.61	0.74	0.86	1.05	1.22	1.36	1.67	117°	108°	110°
ZHGS5.6W	0.307	0.40	0.47	0.56	0.69	0.79	0.97	1.12	1.37	1.58	1.77	2.17	117°	110°	100°
ZHGS8W	0.44	0.57	0.67	0.80	0.98	1.13	1.39	1.60	1.96	2.26	2.53	3.10	118°	110°	103°
ZHGS10W	0.55	0.71	0.84	1.00	1.22	1.41	1.73	2.00	2.45	2.83	3.2	3.9	118°	108°	102°
ZHGS12W	0.66	0.85	1.00	1.20	1.47	1.70	2.08	2.40	2.94	3.4	3.8	4.6	120°	112°	102°
ZHGS14W	0.77	0.99	1.17	1.40	1.71	1.98	2.42	2.80	3.4	4.0	4.4	5.4	118°	114°	104°
ZHGS17W	0.93	1.20	1.42	1.70	2.08	2.40	2.94	3.4	4.2	4.8	5.4	6.6	118°	117°	102°
ZHGS20W	1.10	1.41	1.67	2.00	2.45	2.83	3.5	4.0	4.9	5.7	6.3	7.7	120°	120°	106°
ZHGS24W	1.31	1.70	2.01	2.40	2.94	3.4	4.2	4.8	5.9	6.8	7.6	9.3	122°	118°	106°
ZHGS27W	1.48	1.91	2.26	2.70	3.3	3.8	4.7	5.4	6.6	7.6	8.5	10.5	122°	120°	107°
ZLHGS30W	1.64	2.12	2.51	3.00	3.7	4.2	5.2	6.0	7.3	8.5	9.5	11.6	120°	118°	110°
ZLHGS35W	1.92	2.47	2.93	3.5	4.3	4.9	6.1	7.0	8.6	9.9	11.1	13.6	122°	118°	108°
ZLHGS40W	2.19	2.83	3.3	4.0	4.9	5.7	6.9	8.0	9.8	11.3	12.6	15.5	122°	119°	104°
ZLHGS45W	2.46	3.2	3.8	4.5	5.5	6.4	7.8	9.0	11.0	12.7	14.2	17.4	141°	118°	108°

