




ZF95 SPRAY NOZZLE SPECIFICATIONS

95° SPRAY ANGLE · FLAT SPRAY · QUICK DISCONNECT



Spray angle not exactly as shown

SPRAY CHARACTERISTICS:

ZF95 series spray nozzles produce a flat, fan shaped spray pattern, with a spray angle of 95° at 40 PSI. Spray density tapers off toward the outside of these sprays, to permit overlapping of spray patterns while maintaining uniform spray density.

CONSTRUCTION:

The models listed are machined from bar stock and are one piece construction. Standard materials are brass, 303 stainless steel and 316 stainless steel. Other materials may be available upon request.

NOZZLE PIPE SIZE	Length 'L' (in)	Dim. 'A' (in)
1/8ZF	1.60	0.97
1/4ZF	1.70	0.97
3/8ZF	1.73	0.97
1/2ZF	1.80	0.97
1/2ZLF	2.11	1.25
3/4ZLF	2.19	1.25

TYPICAL APPLICATIONS:

- Parts Cleaning
- Metal Washing
- Foam control
- Gravel Washing
- Vehicle Washing
- Dishwashers
- Fertilizer spraying

Model #	Equiv. Orif. Dia.	Capacities at Various Pressures														Spray Angles		
		5 psi	7 psi	10 psi	15 psi	20 psi	30 psi	40 psi	50 psi	60 psi	80 psi	100 psi	150 psi	200 psi	25 psi	40 psi	50 psi	
ZF9503	0.041	0.106	0.126	0.150	0.184	0.212	0.260	0.300	0.34	0.37	0.42	0.47	0.58	0.82	86	95	101	
ZF9504	0.047	0.141	0.167	0.200	0.245	0.283	0.35	0.40	0.45	0.49	0.57	0.63	0.77	1.10	86	95	101	
ZF9505	0.053	0.177	0.209	0.250	0.306	0.35	0.43	0.50	0.56	0.61	0.71	0.79	0.97	1.37	86	95	101	
ZF9506	0.058	0.212	0.251	0.300	0.37	0.42	0.52	0.60	0.67	0.73	0.85	0.95	1.16	1.64	86	95	101	
ZF9508	0.067	0.283	0.33	0.40	0.49	0.57	0.69	0.80	0.89	0.98	1.13	1.26	1.55	2.19	86	95	100	
ZF9510	0.075	0.71	0.84	1.00	1.22	1.41	1.73	2.00	2.24	2.45	2.83	3.2	3.9	5.5	88	95	99	
ZF9515	0.091	0.53	0.63	0.75	0.92	1.06	1.30	1.50	1.68	1.84	2.12	2.37	2.90	4.1	90	95	100	
ZF9520	0.105	0.71	0.84	1.00	1.22	1.41	1.73	2.00	2.24	2.45	2.83	3.2	3.9	5.5	89	95	99	
ZF9530	0.129	1.06	1.26	1.50	1.84	2.12	2.60	3.00	3.4	3.7	4.2	4.7	5.8	8.2	90	95	101	
ZF9540	0.149	1.41	1.67	2.00	2.45	2.83	3.5	4.0	4.5	4.9	5.7	6.3	7.7	11.0	90	95	100	
ZF9550	0.167	1.77	2.09	2.50	3.06	3.5	4.3	5.0	5.6	6.1	7.1	7.9	9.7	13.7	91	95	101	
ZF9560	0.182	2.12	2.51	3.00	3.7	4.2	5.2	6.0	6.7	7.3	8.5	9.5	11.6	16.4	92	95	102	
ZF9570	0.197	2.47	2.93	3.5	4.3	4.9	6.1	7.0	7.8	8.6	9.9	11.1	13.6	19.2	92	95	103	
ZLF9580	0.211	2.83	3.3	4.0	4.9	5.7	6.9	8.0	8.9	9.8	11.3	12.6	15.5	21.9	92	95	103	
ZLF95100	0.236	3.5	4.2	5.0	6.1	7.1	8.7	10.0	11.2	12.2	14.1	15.8	19.4	27.4	92	95	103	
ZLF95120	0.258	4.2	5.0	6.0	7.3	8.5	10.4	12.0	13.4	14.7	17.0	19.0	23.2	33	92	95	103	
ZLF95150	0.289	5.3	6.3	7.5	9.2	10.6	13.0	15.0	16.8	18.4	21.2	23.7	29.0	41	92	95	102	

* TABLE CONTINUES ON FOLLOWING PAGE



ZF 95 SPRAY NOZZLE SPECIFICATIONS

95 DEGREE SPRAY ANGLE · FLAT SPRAY · QUICK DISCONNECT CONNECTION

www.BEX.com